



Picture (low resolution)	English
	<p>English RAKLE</p> <p>Suspension frame for mid-sized overhead bank lights (up to approx. 90 kg / 198 lbs), control unit not included. Corresponds to MEGA-TRACK ceiling rail system. The trolley is guided on two REGUE rails. Frame and trolley are connected with needle bearings. With 4 individual motors for vertical movement of the frame in all imaginable combinations, and a fifth for rotation.</p> <p>If the bank light proves too heavy for the motors, the cords can be run over hoists to reduce weight and improve mobility.</p> <p>Motorized trolley RUGAI is recommended to ease horizontal displacements of the unit (length- and crosswise)</p> <p>The best up and down results are achieved when the cords connecting the bank light to the frame are almost vertical.</p> <p>All 5 motors: 24 V Weight: approx. 90 kg (198 lbs)</p> <p>Trolley: Length: 100 cm Width: 80 cm</p> <p>Frame: Length: 150 cm Width: 90 cm Rotation: approx. 355° Cord length: 20 m (custom length on request)</p>
<p>Same pictures as RAKLE</p>	<p>RAKLO</p> <p>Same characteristics as suspension frame RAKLE, but with oversize frame for larger (longer and wider) bank lights.</p> <p>Weight: approx. 95 kg (209 lbs)</p> <p>Frame: Length: 200 cm Width: 150 cm Rotation: approx. 355° Cord length: 30 m (custom length on request)</p>
<p>Same pictures as RAKLE</p>	<p>RAKLU</p> <p>Suspension frame for heavy overhead bank lights, up to approx. 160 kg / 353 lbs. Contrary to RAKLE and RAKLO, the trolley is guided on three REGUE rails. Each hoist is equipped with 2 synchronized motors to cope with the additional weight. All other characteristics just like RAKLO.</p> <p>Weight: approx. 110 kg (243 lbs)</p> <p>Trolley: Length: 155 cm Width: 150 cm</p> <p>Frame: Length: 200 cm Width: 150 cm Rotation: approx. 355° Cord length: 40 m (custom length on request)</p>
	<p>RODIU 4</p> <p>Control unit with 4 channels, hand remote over cable. Generally used for ceiling rail motors, e.g. motorized trolley RUGAI or suspension frames RAKLE / RAKLO / RAKLU. Attached directly to trolley RETIU.</p> <p>A transformer, available separately, is required for 110 V mains power supply.</p> <p>Input voltage: 220 V Output voltage: 24 V Length: 17 cm Width: 17 cm Height: 14.5 cm Weight: 5.4 kg (12 lbs)</p>

Picture (low resolution)	English
	<p>RIGUA 5 / 10 / 20 Distance plate 5 / 10 / 20 mm, wood, ROOF-TRACK; for RODIE spacer.</p>
	<p>RIGUO 10 / 20 / 30 Distance plate 10 / 20 / 30 mm, wood, MEGA-TRACK; for RIDIE spacer.</p>
	<p>RUGLO Steel cable fastener for REGUE rail, MEGA-TRACK</p>
	<p>RODOE Rods to connect 2 rails end-to-end, ROOF-TRACK, 1 pair. Length: 26 cm Weight: 330 g (0.7 lbs)</p>